



# INTEGRATED HELMET SYSTEM (IHS) TECHNICAL SPECIFICATION

## BALLISTIC SHELL

<b>Test Standard</b>	Independently Tested to NIJ 0106.01 Protocol for Type IIIA rounds and velocities
<b>Standard Option</b>	2.15 lbs. Shell Weight 3.0 lbs. Full System Weight Aramid Fiber 9mm 124 gr. FMJ - 4 Impacts .44 Magnum 240 gr. SJHP - 4 Impacts 17 gr. V50 ≥ 2058 ft/s
<b>Lightweight Option</b>	1.60 lbs. Shell Weight 2.30 lbs. Full System Weight Polyethylene Composite 9mm 124 gr. FMJ - 4 Impacts .44 Magnum 240 gr. SJHP - 4 Impacts 17 gr. V50 ≥ 2400 ft/s
<b>Sizes Available</b>	Regular X-Large

## RETENTION & SUSPENSION

<b>Retention and Fit</b>	Team Wendy CAM FIT™ BOA closure distributes pressure evenly around the head X-Style nape filled with Zorbium foam
<b>Chin Strap</b>	Locking cam buckles for one-handed adjustment 5/8" nylon webbing with ultra-suede chin cup
<b>Suspension Liner</b>	Team Wendy Epic Air™ Zorbium Foam 3 Piece impact liner with air channels Additional comfort pads

## SHROUD & ACCESSORIES

<b>Shroud</b>	Polymer and Aerospace Grade Metal Composition 0.10 lbs. (1.5 oz) Wilcox® L4 Three Hole Design Quick Release Capability
<b>Bolted Rails &amp; Bungees</b>	Ops-Core® ARC Bolted through Helmet 2 Ops-Core Bungees for securing NVG Emergency Release at 8 ft./lbs.
<b>Velcro Kit</b>	1100 mil-spec Velcro Loop Mil-spec Acrylic Adhesive 4 Piece Configuration
<b>Carry Bag</b>	Houses fully built helmet including comms Durable Cordura Top Zippered Opening Padded Sides



TEAM WENDY



EXPORT CONTROLLED. Body armor, including certain technical data, is controlled for export in accordance with the U.S. Export Administration Regulations (EAR) and the International Traffic in Arms Regulations (ITAR). Diversion contrary to U.S. law is prohibited.